

1.Product overview:

This product is a dual USB charger module with

- (a) It is compatible with Apple, Huawei, Samsung and other leading brands of quick charge protocol (Power Delivery (PD) and Qualcomm Quick Charge (QC 3.0) protocol).
- (b) To have overheat, overcurrent and short-circuit protection.
- (c) To have high efficiency and stable outputs.
- (d) To meet EMC requirement.

2.Instruction for use:

- (a) USB Type-C port support PD and QC.
USB Type-A port support QC.
When both ports are in use, the charger output is 5V.
- (b) LED status indicator:
 - When charger is powered on and without load, the LED is in dim Green.
 - When only USB-A in use, 5V (dim Green), 9V (medium Green), 12V (bright Green).
 - When only USB Type-C in use, 5V (dim Cyan), 9V (medium Blue), 12V (bright Blue).
 - When both ports are in use: 5V (dim Cyan).

1.Product overview:

This product is a dual USB charger module with

- (a) It is compatible with Apple, Huawei, Samsung and other leading brands of quick charge protocol (Power Delivery (PD) and Qualcomm Quick Charge (QC 3.0) protocol).
- (b) To have overheat, overcurrent and short-circuit protection.
- (c) To have high efficiency and stable outputs.
- (d) To meet EMC requirement.

2.Instruction for use:

- (a) USB Type-C port support PD and QC.
USB Type-A port support QC.
When both ports are in use, the charger output is 5V.
- (b) LED status indicator:
 - When charger is powered on and without load, the LED is in dim Green.
 - When only USB-A in use, 5V (dim Green), 9V (medium Green), 12V (bright Green).
 - When only USB Type-C in use, 5V (dim Cyan), 9V (medium Blue), 12V (bright Blue).
 - When both ports are in use: 5V (dim Cyan).