

**T&J ELECTRIC (SINGAPORE) PTE LTD**

Company Registration No: 200205797Z  
10 Ubi Crescent, #02-24, Ubi Techpark, Singapore 408564  
Telephone: +65 6547-4333 Fax: +65 6547-4666

Date: April 3, 2009

**Subject: Product Info: K828 (Shaver Socket) (TM-020022)**

**Features:**

- Dual Voltage Output: 230V and 115V ac.
- Have build-in overload protection to the transformer.
- Supply of power when a plug is inserted into the socket.
- Sockets have interlock shutter to prevent insertion of two plugs at the same time.
- Accept standard European 4mm round pin plug, American flat pin plug and Australian flat pin plug.

**Technical Data:**

- Product Range: Radiance  
All color code for Radiance is applicable on this product.  
Replaceable Frame: K1151
- Comply Standard:  
BS EN 61558
- Rated Voltage:  
Input: 230V ac 50Hz  
Output: 115/230V ac 50Hz



**Front View of K828**

**T&J ELECTRIC (SINGAPORE) PTE LTD**

Company Registration No: 200205797Z  
10 Ubi Crescent, #02-24, Ubi Techpark, Singapore 408564  
Telephone: +65 6547-4333 Fax: +65 6547-4666

Date: April 3, 2009

**Subject: Product Info: K828 (Shaver Socket) (TM-020022)**

---

- Max load: 20VA.
- Terminal Hole: 4mm diameter.  
(Line, Neutral and Earth terminals)
- Operating temperature: -5°C to +40°C
- Dimension: 86 \* 146 mm
- Fix Center: 120.6 mm
- Fix Screws: M3.5 \* 18 mm
- Mounting Box: 48 mm depth or higher
- Package: 1 pc per box, 10 pc per carton



**Rear View of K828**