

**T&J ELECTRIC (SINGAPORE) PTE LTD**

Company Registration No: 200205797Z  
10 Ubi Crescent, #02-24, Ubi Techpark, Singapore 408564  
Telephone: +65 6547-4333 Fax: +65 6547-4666

Date: 1<sup>st</sup> July 2020

**Subject: Product Info: Shaver Socket - infinit HC8688/HC8668**

**Features:**

- Dual Voltage Output:  
230V and 115V AC
- With build-in overload protection
- When a plug is inserted into the socket, then power is supplied
- Sockets have interlock shutter to prevent insertion of two plugs at the same time
- Accept standard European 4mm round pin plug, American flat pin plug and Australian flat pin plug

**Technical Data: HC8688 (86x146mm)**

- Product Range: **infinite**  
All colour codes for infinite is applicable on this product.
- Comply Standard:  
BSEN 61558
- Rated Voltage:  
Input: 230V AC  $\pm 10\%$ , 50Hz  
Output: 115V AC  $\pm 10\%$ , 50Hz  
Output: 230V AC  $\pm 10\%$ , 50Hz
- Max load: **20VA**
- Wire size: 0.5 ~ 1.5mm<sup>2</sup>  
(Recommended for L, N, E terminals)



**Front View of HC8688**



**Rear View of HC8688**

**T&J ELECTRIC (SINGAPORE) PTE LTD**

Company Registration No: 200205797Z  
10 Ubi Crescent, #02-24, Ubi Techpark, Singapore 408564  
Telephone: +65 6547-4333 Fax: +65 6547-4666

Date: 1<sup>st</sup> July 2020

**Subject: Product Info: Shaver Socket - infinit HC8688/HC8668**

- Temperature range: -10°C ~ 45°C
- Dimension: 86 x 146 mm
- Fix Center: 120.6 mm
- Fix Screws: M3.5x0.6x30±
- Mounting Box: >47 mm depth

---

**Technical Data: HC8668 (86x86mm)**

- Product Range: **infinite**  
All colour codes for infinite is applicable on this product.
- Comply Standard:  
BSEN 61558
- Rated Voltage:  
Input: 230V AC ±10%, 50Hz  
Output: 115V AC ±10%, 50Hz  
Output: 230V AC ±10%, 50Hz
- Max load: **15VA**
- Wire size: 0.5 ~ 1.5mm<sup>2</sup>  
(Recommended for L, N, E terminals)
- Temperature range: -10°C ~ 45°C
- Dimension: 86 x 86 mm
- Fix Center: 60.3 mm
- Fix Screws: M3.5x0.6x30±
- Mounting Box: >47 mm depth



**Front View of HC8668**