

T&J ELECTRIC (SINGAPORE) PTE LTD

Company Registration No: 200205797Z
10 Ubi Crescent, #02-24, Ubi Techpark, Singapore 408564
Telephone: +65 6547-4333 Fax: +65 6547-4666

Date: 21st September 2020

Subject: Product Info: Shaver Socket - infinit HC8688/HC8668

Features:

- Dual Voltage Output:
230V and 115V AC
- Double-wound isolating transformer
- Built-in overload protection
- Shaver plug insertion into the socket, output power is automatically on, shaver plug removal, output power is automatically off
- Sockets have interlock shutter to prevent insertion of two plugs at the same time
- Accept standard European 4mm round pin plug, American flat pin plug and Australian flat pin plug

Technical Data: HC8688 (86x146mm)

- Product Range: **infinite**
- Standards:
BS EN 61558
- Rated Voltage:
Input: 230V AC $\pm 10\%$, 50Hz
Output: 115V AC $\pm 10\%$, 50Hz
Output: 230V AC $\pm 10\%$, 50Hz
- Max load: **20VA**
- Wire size: 0.5 ~ 1.5mm²
(Recommended for L, N, E terminals)



Front View of HC8688



Rear View of HC8688

T&J ELECTRIC (SINGAPORE) PTE LTD

Company Registration No: 200205797Z
10 Ubi Crescent, #02-24, Ubi Techpark, Singapore 408564
Telephone: +65 6547-4333 Fax: +65 6547-4666

Date: 21st September 2020

Subject: Product Info: Shaver Socket - infinit HC8688/HC8668

- Temperature range: -10°C ~ 45°C
- Dimension: 86 x 146 mm
- Fix Center: 120.6 mm
- Fix Screws: M3.5x0.6x30±
- Mounting Box: >47 mm depth

Technical Data: HC8668 (86x86mm)

- Product Range: **infinit**
- Standards:
BS EN 61558
- Rated Voltage:
Input: 230V AC ±10%, 50Hz
Output: 115V AC ±10%, 50Hz
Output: 230V AC ±10%, 50Hz
- Max load: **15VA**
- Wire size: 0.5 ~ 1.5mm²
(Recommended for L, N, E terminals)
- Temperature range: -10°C ~ 45°C
- Dimension: 86 x 86 mm
- Fix Center: 60.3 mm
- Fix Screws: M3.5x0.6x30±
- Mounting Box: >47 mm depth



Front View of HC8668

All standard colours for **infinit** is applicable on this product.